



GO RIDE THE NEXT LEVEL K250R ALL OUT



POWERFUL. EFFICIENT. DURABLE

The 3rd Generation Kibo K250R

go do >>> more

The Bike's Specifications

Engine Type	4-stroke SOHC internal combustion engine
Bore and Stroke	65.5mm x 66.2 mm
Compression Ratio	9.2:1
Maximum Power Output	17.4 HP at 6500 RPM
Maximum Torque	20.7 Nm at 5200 RPM
Engine Capacity	250.2cc
Chassis	Hybrid backbone cradle frame
Ignition System	CDI
Starter	Electric starter and kick starter
Transmission	5-speed constant mesh
Dimensions	2200 mm x 855 mm x 1200 mm
Wheel Base	1450 mm
Seat Height	815 mm
Ground Clearance	200 mm
Fuel Capacity	13.4 L
Fuel Economy	33 km/l
Front Tire	90/90 - 21 inch, tube type
Rear Tire	5.10-18 inch tube type
Front Suspension	Telescopic front fork, 215 mm travel
Rear Suspension	Twin coil-over shocks, 140 mm travel
Front Brakes	Single disc (266 mm), dual piston brake, floating caliper
Rear Brakes	Single disc (215 mm), dual piston brake, floating caliper
Maximum Carrying Load	250 kg
Kerb Weight	156 kg
USB Charger	Dual port, 5V 2.1A

› STRONG

Meet your ultimate ride: the Kibo K250R. Tough, agile, and engineered for strength with a trellis frame capable of securely carrying heavy loads up to 250kg.

› EFFICIENT

Efficiency is optimized through a 250.2cc oil-cooled, single-cylinder engine, with an enhanced engine temperature regulation. Making it more efficient than the air-cooled engines without a radiator. Enjoy a perfect mix of power and efficiency with an improved average fuel consumption of 33 km/l. It incorporates a balance shaft that significantly diminishes engine vibration, resulting in a smoother ride.

› COMFORTABLE

The Kibo K250R's 215 mm front suspension travel offers enhanced riding comfort. Its 21-inch diameter front wheel rides over big obstacles easily. It is fitted with 21" front and 18" rear tires, designed for mixed terrain use, providing a smooth ride on-road and great traction on trails.

› SAFE

Ride confident backed by the outstanding braking power of the Kibo K250R. Equipped with 266 mm front disc and 215 mm rear disc hydraulic brake system, specifically developed for the K250R's high load carrying capacity. Rider visibility is enhanced by rear LED lights and turn signals. It comes standard with a crisp digital display that shows you everything you need to know in one quick glance.

For more information contact us on:
0723 737 977 | sales@kibo.bike
www.kibo.bike